



COLORS AVAILABLE

- Neutral
- Black
- Blue
- Green
- Yellow
- Red

CHEMICAL RESISTANCE

- Oils and fats, fuels, lubricants
- Hydraulic fluids
- Non-chlorine cleaning agents and solvents
- Diluted organic acids
- Very mild mineral acids, bases and salt solutions

APPLICATION

- Compressed air
- Hydraulics
- Negative pressure
- Cooling lines fuel and lubricant systems

PROPERTIES

- Wide temperature and application range
- Colour black: UV resistant
- Pressure and impact resistant
- Good chemical resistance
- Smooth surface
- Also available in PA6 (high pressure)

Is available on request in other lengths than the standard coil.

TECHNICAL SPECIFICATIONS

| | |
|----------------------|--------------|
| Temperature Range °C | -40 to + 100 |
| Material | PA |

PRODUCT INFORMATION

| Size | P | D | d | s | Bending radius | MOQ | kg/100m |
|-------------|----|-------|-------|------|----------------|------|---------|
| 4/2x1 | 44 | 4.00 | 2.00 | 1.00 | 15.0 | 100m | 0.970 |
| 5/3x1 | 33 | 5.00 | 3.00 | 1.00 | 30.0 | 100m | 1.140 |
| 6/4x1 | 26 | 6.00 | 4.00 | 1.00 | 27.0 | 100m | 1.620 |
| 6/4x1 | 26 | 6.00 | 4.00 | 1.00 | 27.0 | 500m | 1.620 |
| 6.35/4.35x1 | 26 | 6.35 | 4.35 | 1.00 | 27.0 | 100m | 1.810 |
| 8/6x1 | 19 | 8.00 | 6.00 | 1.00 | 40.0 | 100m | 2.270 |
| 10/8x1 | 19 | 10.00 | 8.00 | 1.00 | 60.0 | 50m | 2.910 |
| 10/7x1.5 | 24 | 10.00 | 7.00 | 1.50 | 45.0 | 50m | 3.540 |
| 12/10x1.5 | 12 | 12.00 | 10.00 | 1.00 | 85.0 | 50m | 4.000 |
| 12/9x1.5 | 19 | 12.00 | 9.00 | 1.50 | 70.0 | 50m | 5.100 |
| 15/12x1.5 | 15 | 15.00 | 12.00 | 1.50 | 100.0 | 50m | 6.570 |

Bar= operating pressure at 23 °C

- MOQ = Minimum order quantity
- P = pressure (bar)
- D = tube outside diameter (mm)
- d = tube inside diameter (mm)
- s = wall thickness (mm)

