



COLORS AVAILABLE

- Black

CHEMICAL RESISTANCE

- UV resistant

APPLICATION

- Pneumatics
- Humid and wet environments

DEBURRING TOOL

To use Dekabon properly we advise to use the deburring tool



PROPERTIES

- Multilayer tube of PE and aluminium core
- Can be bent manually
- Retains shape
- Lightweight yet sturdy

TECHNICAL SPECIFICATIONS

Temperature Range °C	-20 to + 80
Material	DEKA

PRODUCT INFORMATION

Size	P	D	d	s	Bending radius	MOQ	kg/100m
6	34	6.00	3.90	1.05	19.0	100m	2.000
6	34	6.00	3.90	1.05	19.0	300m	2.000
6.35	34	6.35	4.30	1.00	19.0	100m	2.400
6.35	34	6.35	4.30	1.00	19.0	300m	2.400
8	34	8.00	5.30	1.35	25.0	100m	3.200
8	34	8.00	5.30	1.35	25.0	300m	3.200
9,52(3/8)	34	9.52	6.30	4.62	32.0	75m	5.200
10	34	10.00	6.20	1.90	32.0	100m	5.700
10	34	10.00	6.20	1.90	32.0	300m	5.700
12	20	12.00	8.20	1.90	40.0	100m	7.500
12,7(1/2)	20	12.70	9.50	1.60	40.0	75m	7.300
14	20	14.00	9.80	2.10	63.0	100m	9.600
15	16	15.00	10.70	2.15	70.0	100m	10.600

Bar= operating pressure at 23 °C

- MOQ = Minimum order quantity
- P = pressure (bar)
- D = tube outside diameter (mm)
- d = tube inside diameter (mm)
- s = wall thickness (mm)

